

STONE PRO

GP3 GRANITE POLISH

Granite Polishing Cream



A professional grade polishing compound designed specifically for restoration of granite surfaces.

- Restores polish and shine
- A unique blend of abrasives and polishing agents
- Also works on engineered stone
- For professional use only

Application Instructions:

Countertops

1. Make sure surface is clean and free of any debris.
2. Use 1 teaspoon of GP3 per 2 square foot area.
3. Use a low-speed (600-800 RPM) variable speed polisher and a white pad.
4. Starting slowly spread polish evenly over the surface until the GP3 starts to dry out.
5. As GP3 dries out, increase speed and lower pressure.
6. Buff until GP3 is completely gone.
7. If any swirls or marks appear because too much product was used, remove the swirls/marks with a clean white pad and a mist of water.

Floors

1. Make sure surface is clean and free of any debris.
2. If surface needs to be restored, hone the surface with diamond abrasive pads to at least 800 grit.
3. Measure 2-4 teaspoons for every 4-8 sq. ft.
4. Use a low-speed (175 RPM) floor machine wheighted (135 lbs.) and a white pad.
5. Starting slowly spread polish evenly over the surface until the GP3 starts to dry out.
6. Spread GP3 evenly over the surface until GP3 starts to dry out and stone becomes shiny.
7. Buff until GP3 is completely gone.
8. If any swirls or marks appear because too much product was used, remove the swirls/marks with a clean white pad and a mist of water.



SCAN TO
WATCH
HOW-TO
VIDEO

