

STONE PRO

SAFE GUARD H₂O

Penetrating Sealer

Water based sealer for **TILE, GROUT, BRICK** and **CONCRETE**. Excellent water repellent for interior and exterior surfaces.



For Use On:

Concrete, masonry, saltillo, flagstone, stucco, quarry tile, brick, tile, grout and natural stone surfaces

Available Sizes:

Gallon, 5 gallon & 55 gallon

Coverage:

400 - 1,000 sq. ft. per gallon.

Coverage will vary based on the porosity & texture of the surface

S-SGH20G, S-SGH205G, S-SGH2055G

PRODUCT FEATURES:

- Water Based
- Non-Flammable
- Environmentally Safe
- Long Lasting
- Will not change color or appearance of surface
- VOC compliant - Meets or exceeds all EPA, SCAQMD, State and County requirements

www.StoneProOnline.com

Application Instructions:

- 1) Liberally apply an even coat to surface. Sealer should saturate evenly to ensure proper penetration.
- 2) Allow sealer to penetrate surface for 3 - 5 minutes. Surface should remain wet with sealer for 5 minutes.
- 3) After 5 minutes, wipe any remaining sealer from the surface.
- 4) Avoid contact with surface for 3 - 5 hour or until surface is completely dry.
- 5) Achieves full cure and repellency in 24 - 72 hours

HANDLING AND STORAGE: Close container tightly after each use. Store in original container only. Store and use in temperatures between 50F and 80F.

