

**Stone Pro Wet Poultice  
Oil and Stain Remover**

Revision nr. 1

Dated 10/21/2015

Printed on 10/21/2015

Page n. 1/9

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Wet Poultice (OIL STAIN REMOVER)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**  
Intended use Absorbing Paste for Stain and oil Removing. not dangerous.

#### 1.3. Details of the supplier of the safety data sheet

Company Name Stone Pro  
Full address 1810 E. Ball Road, Anaheim, CA 92805

Tel. 866-786-6310  
Fax 714-422-1105

**1.4. Emergency telephone number** CALL INFOTRAC 800-535-5053

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

##### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

#### 2.2. Label elements.

Hazard pictograms: --

Signal words: --

Hazard statements:

--

Precautionary statements:

# Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on  
10/21/2015  
Page n. 2/9

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

## 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
2-BUTOXYETHANOL			
CAS. 111-76-2	0 - 4	Xn R20/21/22, Xi R36/38	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

Not specifically necessary. Observance of good industrial hygiene is recommended.

### 4.2. Most important symptoms and effects, both acute and delayed.

No episodes of damage to health ascribable to the product have been reported.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters.

# Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on  
10/21/2015  
Page n. 3/9

## GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

### 7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

AUS	Österreich	Grenzwerteverordnung 2011 - GKV 2011
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail 2012. / Grenzwerte am Arbeitsplatz
CYP	Κύπρος	Κ.Δ.Π. 268/2001; Κ.Δ.Π. 55/2004; Κ.Δ.Π. 295/2007; Κ.Δ.Π. 70/2012
CZE	Česká Republika	Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
DNK	Danmark	Graensevaerdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015

## Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on 10/021/2015

Page n. 4/9

FIN	Suomi	HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisuja 2012:5
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 20. júna 2007
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

### 2-BUTOXYETHANOL

#### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	98	20	200	40	SKIN.
VLEP	BEL	98	20	246	50	SKIN.
TLV	BGR	98		246		SKIN.
VEL	CHE	49	10	98	20	SKIN.
MAK	CHE	49	10	98	20	SKIN.
TLV	CYP	98	20	246	50	SKIN.
TLV	CZE	100		200		SKIN.
AGW	DEU	49	10	196	40	SKIN.
MAK	DEU	49	10	98	20	SKIN.
TLV	DNK	98	20			SKIN.
VLA	ESP	98	20	245	50	SKIN.
HTP	FIN	98	20	246	50	SKIN.
VLEP	FRA	49	10	246	50	SKIN.
WEL	GRB	123	25	246	50	SKIN.
TLV	GRC	120	25			
OEL	IRL	98	20	246	50	SKIN.
TLV	ITA	98	20	246	50	SKIN.
OEL	NLD	100		246		SKIN.
NDS	POL	98		200		
NPHV	SVK	98	20	246		SKIN.
MAK	SWE	50	10	100	20	SKIN.
OEL	EU	98	20	246	50	SKIN.
TLV-ACGIH		97	20			

#### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 97 mg/m3.

# Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on 10/021/2015

Page 5/9

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	paste
Colour	light grey
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not applicable.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,100 Kg/l
Solubility	insoluble
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2. Other information.

VOC (Directive 1999/13/EC) :	0,77 % - 8,6 g/litre.
VOC (volatile carbon) :	0,48 % - 5,06 g/litre.

# Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on 10/021/2015

Page 6/9

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.  
2-BUTOXYETHANOL: decomposes in the presence of heat.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.  
2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.

### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.  
2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

### 10.5. Incompatible materials.

Information not available.

### 10.6. Hazardous decomposition products.

2-BUTOXYETHANOL: hydrogen.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

2-BUTOXYETHANOL  
LD50 (Oral).615 mg/kg Rat  
LD50 (Dermal).405 mg/kg Rabbit  
LC50 (Inhalation).2,2 mg/l/4h Rat

## SECTION 12. Ecological information.

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

2-BUTOXYETHANOL

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

### 12.3. Bioaccumulative potential.

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water. 0,81

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

**Stone Pro Wet Poultice  
Oil and Stain Remover**

Revision nr. 1

Dated 10/21/2015

Printed on 10/021/2015

Page 7/9

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

### 14.1. UN number.

Not applicable.

### 14.2. UN proper shipping name.

Not applicable.

### 14.3. Transport hazard class(es).

Not applicable.

### 14.4. Packing group.

Not applicable.

### 14.5. Environmental hazards.

Not applicable.

### 14.6. Special precautions for user.

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

## SECTION 15. Regulatory information.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category

None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

# Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on 10/021/2015

Page 8/9

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>EUH210</b>	Safety data sheet available on request.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

<b>R20/21/22</b>	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
<b>R36/38</b>	IRRITATING TO EYES AND SKIN.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration



## Stone Pro Wet Poultice Oil and Stain Remover

Revision nr. 1

Dated 10/21/2015

Printed on 10/021/2015

Page 9/9

- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
  2. Directive 67/548/EEC and following amendments and adjustments
  3. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  4. Regulation (EU) 1272/2008 (CLP) of the European Parliament
  5. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  6. Regulation (EU) 453/2010 of the European Parliament
  7. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  8. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  9. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  10. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  11. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - Niosh - Registry of Toxic Effects of Chemical Substances
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.